

TE-RTD12

MOTOR RTD MONITORING DEVICE

+ Differential Protection



Advanced Motor Temperature Monitoring Preventive Maintenance

- Can be located at the motor
- Reduced wiring
- Vibration detection via 4-20mA inputs
- Remote monitoring optional
- Digitally communicates with the MVC
- MLink compatible for easy setup



Advanced Motor RTD + Differential Protection

Resistance Temperature Dectector (RTD) + Differential Protection

The TE-RTD12 Relay device adds advanced RTD (Resistor Temperature Detector) and differential current monitoring capability to your new or existing motor system. The TE-RTD12 Relay device offers 12 built-in RTD inputs, 3 programmable output relays (5A), 2 isolated analog inputs (4-20mA), 1 isolated analog output (4-20mA), 3 isolated digital inputs, and differential current monitoring.

Additionally, an RS485 (2 wire) communication port is available for use with a master device (PLC / SCADA / Operator Interface) for the purpose of programming and/or monitoring.

Programmable relay outputs are provided that can be configured for a system function or for use as a global Alarm or Trip based on temperature readout, which can be entered in °C or °F.

A built-in event recorder stores fault history of past events with data points including Alarm Code , Trip Code, Current , Temperature value, Analog input value and Date / Time Stamp.



Specifications

Control Voltage:	Universal input range 120 – 240 VAC 50/60Hz
Inputs:	12 RTD inputs (Pt100, Ni100, Ni120, Cu10), 3 CT inputs for differential CT's 2 isolated 4-20mA analog inputs ¹ , 3 isolated Digital Inputs ²
Outputs:	3 programmable form C Relays with 5A contact rating and 1 isolated 4-20mA analog output
Keypad:	Two 4-digit displays, one for RTD name, one for Temperature, LEDs for OK, ALARM & TRIP, 3 Output Relay LEDs, Easy to use pushbutton keypad for customer interface.
Differential CT's:	Primary 5-2000A, Secondary 1A or 5A, Alarm and Trip Levels OFF, 5% to 90 % of CT value
Resolution/Accuracy:	Analog Inputs better than 1%, Analog Outputs better than 0.5%
Communication Port:	2 Wire RS-485 ² , MODBUS RTU
I/O Terminals:	Removable terminal blocks
Temperature:	Operating 32°F – 122°F / 0°C to 50°C, Storage -4°F to 176°F / -20°C to 80°C

¹ All analog I/O share a common ground point

² RS485 and Digital Inputs share a common ground point



TE-RTD12 Series

USA HEADQUARTERS

Motortronics / Phasetronics

1600 Sunshine Drive
Clearwater, Florida 33765
USA

Tel: + 727-573-1819 / 888-767-7792

Fax: + 727-573-1803 / 800-548-4104

E-mail: sales@motortronics.com

www.motortronics.com

UNITED KINGDOM

Motortronics UK

Bristow House,
Gillard Way, Ivybridge,
Devon, PL21 9GG,
United Kingdom

Tel: +44 (0)1752-894554

www.motortronics-uk.co.uk

SOUTH KOREA

Motortronics Int'l Korea Co Ltd

#1607, 128 Gasan digital 1-ro,
Gasan digital 1-ro,
Geumcheon-gu,
Seoul 08507, Republic of Korea

Tel: 82-2-867-5808

Fax: 82-2-867-6004

www.motortronics-korea.com

CHINA

M & P Machinery & Electronics Control

Part of the Motortronics Group

32 Jiaxin Road,
Jimo,
Qingdao, China 266229

Tel: 86-532-81725028

Fax: 86-532-81725038

www.mp-cn.com

UNITED ARAB EMIRATES

Motortronics MEA, LLC

Sharjah Media City,
Sharjah,
United Arab Emirates

Tel: +1 971-50 763 4920

www.motortronics.com

PN: TE-RTD12-080620